



## P3L

Cost-effective thermal receipt printer delivering performance, flexibility, and reliability

The affordable P3L thermal receipt printer is the perfect solution for businesses looking for reliable performance and flexibility. Designed to support existing and new applications with its triple interface design, the P3L supports USB, serial, and ethernet connectivity. Ideal for retail and hospitality, the P3L's 250mm/second print speed ensures quick transactions at the point-of-sale. Built for longevity, it is equipped with a long-life print head and autocutter. Engineered utilizing Custom's 30+ years of printing expertise, the P3L is the leader for cost-effective thermal POS printers.



## CHARACTERISTICS

1. **Triple Interface**  
The P3L comes standard with USB, Serial, and Ethernet interfaces for maximum connectivity
2. **250mm/s Print Speed**  
With a print speed of 250mm/s, the P3L will save your business time at the checkout
3. **Cost Effective**  
The easy-to-use P3L is our most cost-effective POS receipt printer and includes both USB and Serial interface cables
4. **Durable**  
Leveraging Custom's 30+ years of printing expertise, the P3L features a long-life print head and autocutter
5. **CUSTOM/POS and OPOS Compatible**  
Supporting both CUSTOM/POS and OPOS, the P3L is an easy drop-in replacement for the majority of POS applications

## MARKETS

- Retail
  - Hospitality
-

## TECHNICAL SHEET

<b>Printing Method</b>	Thermal printing, fixed head
<b>Number of dots</b>	8 dots / mm
<b>Resolution</b>	203dpi
<b>Printing (mm/sec)</b>	200mm/s
<b>Auto-cutter</b>	Cutter life 1.5 million cuts Partial cut
<b>Printing Direction</b>	Normal, 90°, 180°, 270°
<b>Printing Format</b>	Height and width from 1 to 8, bold, reverse, underlined, italic
<b>Character set</b>	Standard font, Extended Chinese GB18030-2000
<b>Supported Barcode</b>	1D: UPC-A, UPC-E, EAN8, EAN13, CODE39, ITF, I25, CODABAR, CODE128, CODE11, MSI 2D: PDF417, QRCODE, DATAMATRIX
<b>Paper width</b>	58mm / 80mm
<b>Sensors</b>	Low paper
<b>Emulation</b>	CUSTOM/POS
<b>Interfaces</b>	USB type B RS232 DB9 Ethernet RJ45 Cash drawer RJ12, 24V
<b>Drivers</b>	Windows® (32/64 bit) Linux (32/64 bit)
<b>Tool software</b>	PrinterTool
<b>Power supply</b>	External 24 Vdc ± 10%
<b>Medium consumption</b>	2.5A (12,5% dots turned on)
<b>Head Life</b>	150 Km
<b>Operating temperature</b>	0°C + 45°C
<b>Dimensions</b>	196 mm (W) × 144 mm (L) × 148 mm (H)
<b>Weight</b>	1 Kg

## MODELS



**911MX010200733**  
PRINTER P3L 80MM ETH USB  
RS232



**911MX010100733**  
PRINTER P3L 80MM ETH USB  
RS232 USA



**911MX010400733**  
PRINTER P3L 80MM ETH USB  
RS232 BRA

Via Berettine, 2 - 43010 Fontevivo PR - VAT: IT02498250345 - TEL: +39 0521 680111 - FAX: +39 0521 610701 - UNIQUE CODE: 8RQN7AZ

The technical data on this website are not binding and may be changed without advanced notice.

Last update: 28 September 2022