

- “Designed for Touch” from the ground up
- Stable stand and tiltable display
- Intel dual processor
- 3 year standard warranty



## B-Series B3 Rev.B All-in-One Touchcomputers

The Elo Touch Solutions B-Series B3 Rev.B models provide a compact, configurable, ruggedized touchcomputer in two screen sizes: 15-inch and 17-inch. These models are available with a choice of industry-leading Elo touch technologies: AccuTouch (“no-bezel” resistive) or iTouch Plus (zero-bezel multi-touch surface acoustic wave).

The B-Series B3 models have been developed to meet the diverse needs of a wide variety of point-of-sale (POS), point-of-information (POI), and point-of-service venues, including retail and hospitality display units, customer loyalty systems, internet access sites and mobile kiosks.

B-Series B3 touchcomputers have a compact, stylish design, with a choice of configuration and customer-installable peripheral options as well as ease of serviceability. These models feature a fan-cooled 3rd Generation Intel Core-i3, 3.3GHz i3-3220 processor with HD2500 graphics, and support multiple customer-installable memory and storage configurations.

Also available to complement the B3 is the fan-less B2 touchcomputer, available with the Intel Atom Dual-Core 1.86GHz N2800 processor.



## PRODUCT OVERVIEW

### Features

- Small footprint, retail-hardened, flexible touchcomputer
- Full range of standard connectivity ports for retail POS/POI and hospitality applications
- Customer-installable peripheral, memory and storage options
- Choice of industry-leading Elo touch technologies: AccuTouch and iTouch Plus

### Benefits

- Outstanding configurability and customization options to meet all your connectivity needs
- Zero-bezel models provide a seamless, edge-to-edge design for a sleek appearance that is easy to clean and maintain
- Stability to withstand the rigors of use in a public environment

### About Elo

Elo founders pioneered the touch screen over 40 years ago. Today, Elo Touch Solutions is a leading global supplier of touch-enabled technology, products and industry solutions. The Elo portfolio encompasses the broadest selection of OEM touchscreen components, touchmonitors, and all-in-one touchcomputers for the demanding requirements of diverse markets, including gaming machines, hospitality systems, industrial automation, interactive kiosks, healthcare, office equipment, point of sale terminals, retail displays, and transportation applications. The Elo touch experience has consistently stood for quality, reliability and innovation with over 20 million installations worldwide.

## B-Series B3 Rev.B All-in-One Touchcomputers

| Computer Specifications  | 15B3 15-inch model   | 17B3 17-inch model  |
|--|--|---|
| Enclosure Color  | Dark grey  |   |
| Processor  | 3rd Generation Intel Core-i3 3.3GHz i3-3220 (Ivy Bridge); 3MB Intel Smart Cache; 5 GT/s Direct Media Interface (DMI)                                     |   |
| Memory (RAM)   | 2GB 1333MHz DDR3 SO-DIMM on 1 of 2 slots. Expandable to 8GB  |   |
| Chipset  | Intel H61 Express  |   |
| Video  | Intel HD Graphics 2500   |   |
| Display  | 15.0" diagonal, Active matrix TFT LCD (CCFL), 4 x 3  | 17.0" diagonal, Active matrix TFT LCD (LED), 5 x 4                                      |
| Useful Screen Area (W x H)   | 12.0" x 9.0" (304.0mm x 228.0mm)   | 13.3" x 10.6" (338.0mm x 270.0mm)   |
| Native (optimal) Resolution  | 1024 x 768   | 1280 x 1024   |
| Colors   | 16.7 million   |   |
| Brightness (typical)   | LCD panel: 250 nits; AccuTouch: 200 nits; iTouch Plus: 225 nits  |   |
| Response Time-total (typical)  | 8 ms   | 5 ms  |
| Viewing Angle (typical)  | Horizontal: ±70° or 140° total; Vertical: 60°/65° or 125° total  | Horizontal: ±80° or 160° total; Vertical: ±80° or 160° total                            |
| Contrast Ratio (typical)   | 700:1  | 1000:1  |
| Controls (bottom)  | Power, brightness up, brightness down, volume up, volume down  |   |
| Security Lockouts  | Power and control buttons lock   |   |
| Available Touch Technologies   | AccuTouch ("no-bezel" resistive); iTouch Plus (zero-bezel multi-touch surface acoustic wave)   |   |
| Serial Ports   | 2 x Native RS-232  |   |
| USB Ports  | 6 x USB 2.0 (4 on I/O, 1 x USB side access, 1 x USB hidden/protected). (Additional internal ports available for optional Elo peripherals.)               |   |
| Ethernet Port  | 1 x LAN RJ45 (Gigabit)   |   |
| Cash Drawer Port   | Built-in 12V/24V Cash Drawer Port (24V default; selectable via jumper)   |   |
| Audio Ports  | 1 x 3.5mm line-in; 1 x 3.5mm line-out; 1 x 3.5mm mic-in  |   |
| Speakers   | Two 2W internal speakers   |   |
| Hard Disk Drive  | 320GB 2.5" 5400rpm Advanced Format (4K) SATA HDD   |   |
| Operating System Options   | No Operating System; Microsoft Windows XP Professional Service Pack 3 (32-bit only); Microsoft Windows 7 Professional Service Pack 1 (64-bit and 32-bit) |   |
| Touchcomputer Dimensions (max. with stand, dimensions, vary with tilt and options) | 14.0" x 10.5" x 14.3" (354.4mm x 267mm x 363.5mm)  | 15.2" x 10.5" x 14.2" (386.4mm x 267mm x 361.0mm)                                       |
| Weight   | With stand: 19.1lbs (8.7kg); without stand: 14.3lbs (6.5kg); shipping: 25.8lbs (11.7kg)  | With stand: 20.9lbs (9.5kg); without stand: 16.1lbs (7.3kg); shipping: 27.5lbs (12.5kg) |
| Shipping Box Dimensions  | 17.4" x 10.2" x 21.9" (443mm x 258mm x 555mm)  |   |
| Power Consumption (max.)   | 70W (without peripherals)  | 71W (without peripherals)   |
| Temperature  | Operating: 32°F to 95°F (0°C to 35°C); Storage -4°F to 140°F (-20°C to 60°C)   |   |
| Humidity (non-condensing)  | Operating: 20% to 80%; Storage: 5% to 95%  |   |
| Warranty   | 3 years  |   |
| MTBF   | 50,000 hours demonstrated  |   |
| Cables and Accessories   | North American and European power cables included  |   |
| Power Supply   | External 12VDC universal-type power supply brick; AC input voltage: 100-240VAC; Input frequency: 50-60Hz; max. output power: 150W (max. draw: 170W)      |   |
| Agency Certification   | UL/cUL, FCC, TUV, CE, CB, Mexico COC, Argentina S-mark (power brick only), C-Tick, VCCI  |   |

## Ordering Information

| Technology  | Operating System | Region                      | Part Number |             |
|-------------|------------------|-----------------------------|-------------|-------------|
|             |                  |                             | 15" Display | 17" Display |
| AccuTouch   | Dark Grey        | None                        | Worldwide   | E051651     |
|             | Dark Grey        | Windows XP Pro SP3 (32-bit) | Worldwide   | E041642     |
|             | Dark Grey        | Windows 7 Pro SP1 (64-bit)  | Worldwide   | E719553     |
| iTouch Plus | Dark Grey        | None                        | Worldwide   | E792415     |
|             | Dark Grey        | Windows XP Pro SP3 (32-bit) | Worldwide   | E010116     |
|             | Dark Grey        | Windows 7 Pro SP1 (64-bit)  | Worldwide   | E406366     |

To find out more about our extensive range of Elo touch solutions, go to [www.elotouch.com](http://www.elotouch.com), or call the office nearest you.

### North America

Elo Touch Solutions  
1033 McCarthy Boulevard  
Milpitas, CA 95035

### 800-ELO-TOUCH

Tel +1 408 597 8000  
Fax +1 408 597 8001  
customerservice@elotouch.com

### Europe

Tel +32 (0)16 70 45 00  
Fax +32 (0)16 70 45 49  
elosales@elotouch.com

### Asia-Pacific

Tel +86 (21) 3329 1385  
Fax +86 (21) 3329 1400  
www.elotouch.com.cn

### Latin America

Tel 786-923-0251  
Fax 305-931-0124  
www.elotouch.com

Elo Touch Solutions, Inc. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo (logo) and Elo Touch Solutions are trademarks of Elo Touch Solutions, Inc. Copyright 2013 Elo Touch Solutions, Inc. All rights reserved. DS000034, rev B 10/13

