SUNMI MAX Cash Drawer

Maximize your potential.

MAX capacity, smarter cash handling.

The cash drawer's front media slot, 5 bill trays, 4 fixed and 6 removable coin trays, making the drawer compatible with over 20 currencies.

MAX durability, more stable.

Adopted high-toughness and rust-free ABS polymer, trapezoidal shape and internal honeycombs, Max Cash Drawer can bear 10kg.

Directly open the drawer with a cash drawer trigger.

USB and Bluetooth enabled. You can open your cash drawer even with no dedicated POS terminal.

MAX experience, minimized nuisance.

The rear cable drawer keeps your countertop tidy. Its hidden rails and durable rollers allow a smooth and quiet opening and closing of the drawer.

Over 1,000,000 operations supported.

MAX security with multiple protections

3-position lock equipped. The drawer can operate on a wide range of voltages, avoiding the risk of damaging the drawer due to voltage mismatch.

Customize reminders with APIs.

It can be integrated with POS apps to let you know your drawer open/close status anytime from anywhere, thus to further ensure your cash security.



MAX capacity, smarter cash handling.

With **5** bill trays, **4** fixed and **6** removable coin trays, MAX Cash Drawer is designed for your booming business.



SUNMI MAX Cash Drawer Tech Specs

General Configuration

Cash Drawer

Bill Clip Plastic and metallic

Drive Protections

3A Overcurrent Protection Input Pulse Overvoltage Protection Input Pulse Timeout Protection Self-Adaptive to 9V-28V Input Voltage Contact ESD 8KV / Air ESD 15KV Thermal Shutdown

Weight

5.8 Kg

Trays

5 bill trays, 1 media slot 4 fixed & 6 removable coin trays

Cable Storage Rear-set drawer

Service Life ≥One million operations **Cable** RJ12, 6P4C, 0.8m

Drive Voltage DC9V~24V, 1A

Status Feedback
Status detection switch

Lock 3-position lock

3-position lock (Open by driver/by key/lock)

Drive Pulse Width

100ms-300ms

Environment

Operating temperature and humidity: $0^{\circ}C \sim 45^{\circ}C$, $30\% \sim 85\%$ Storage temperature and humidity: $-20^{\circ}C \sim 60^{\circ}C$, $10\% \sim 90\%$

Dimensions W430mm x L457mm x H88mm